

Uni-Aluprotect MC

Description:

Uni-Aluprotect MC is a single component, moisture curing, aluminum filled, urethane primer, intermediate coating or finish. The product has very high surface wetting properties.

- * Excellent adhesion to most substrates
- * Low temperature application - down to -10°C
- * Excellent durability
- * Outstanding abrasion resistance
- * Excellent corrosion and chemical resistance

Recommended Usage:

For use over prepared surfaces in Industrial and/or marine environments:

- + Heavy duty interior and exterior structural coating
- + High performance, one coat or multiple coat
- + Coating for steel, aluminum, concrete, and most plastics
- + Universal primer for poorly prepared surfaces, old paint, tightly adherent rust, weathered galvanized steel and concrete
- + Excellent intermediate coat providing superior adhesion of subsequent coats

Works well with:

Iron, Steel, Aluminum, Galvanized Steel, Concrete, Masonry & Previously Painted Surfaces

Application Conditions:

Temperature

Air and Surface : -7°C (20°F) minimum, 38°C (100°F) maximum.

Relative humidity: 20% minimum, 99% maximum

Application Equipment:

Airless spray, Brush or Roller

Ordering Information:

Packaging: 1, 2½, 5, 10 and 20 Litre Cans.

Weight: 1,25 ± 0,05/ liter

Address
Unica Coatings AB
Hamngatan 23 B
S-471 32 Skårhamn

Fax
+46 (0)31 726 77 84

E-mail
sales@unicacoatings.se

www.unicacoatings.se