

Uni-Micazinc MC

Description:

Uni-Micazinc MC is a single component, moisture curing, zinc primer. With enhanced coating strength and edge protection due to the micaceous iron oxide addition. Specially designed for low temperature application to steel surfaces

- * High resistance to mud cracking
- * Easy to apply and no re coat restrictions
- * Excellent durability
- * Outstanding abrasion resistance
- * Very high corrosion resistance and adhesion

Recommended Usage:

For use over prepared surfaces in Industrial and/or marine environments:

- + As a primer in a coating system for bridges, tanks, chemical, and marine structures
- + Ideal for priming water assisted abrasive blasted surfaces where flash rusting or blooming limits the use of conventional zinc rich coatings
- + Primer for poorly prepared surfaces, old paint, tightly adherent rust.
- + In a system meets the requirements in ISO 12944-6 C5M and Norsok 501.

Works well with:

Iron & Steel Immersion and atmospheric service

Application Conditions:

Temperature

Air and Surface : -7°C (20°F) minimum, 38°C (100°F) maximum.

Relative humidity: 20% minimum, 99% maximum

Application Equipment:

Airless spray, Brush or Roller

Ordering Information:

Packaging: 1, 2½, 5 and 10 Liter Cans.

Weight: 2,45 ± 0,05 kg/liter

Address
Unica Coatings AB
Hamngatan 23 B
S-471 32 Skårhamn

Fax
+46 (0)31 726 77 84

E-mail
sales@unicacoatings.se

www.unicacoatings.se